

TREATMENT INSTRUCTIONS

Aircraft Engine Treatment Instructions

NOTE: Read through the entire instruction sheet before installing any Microlon Products.

To Install the Microlon Products-

- 1) Change your oil and oil filter. Change your fuel filter if possible.**
- 2) After the fueling and pre-flight inspection have been completed, bring the engine to operating temperature and shut the engine down.**
- 3) Shake the Microlon containers for at least one minute.**
- 4) Add the Microlon Engine Treatment but do not exceed 20% of the total oil volume at any one time. It may be necessary to add the remaining product after the cleaners have done their job and left the engine.**
- 5) If your aircraft has multiple fuel tanks, add the Microlon Fuel Treatment to a 1/2 tank of fuel or less. Run that tank as low as possible during the run-in time before switching. If your aircraft has a single fuel tank, add the fuel treatment to that tank.**
- 6) Start up the engine and immediately fly for at least 2 hours. If any remaining engine treatment needs to be added later, repeat these steps and operate the engine for another two hours.**

NOTE: Do not change your oil for at least 15 flying hours after treatment to make sure that you get the full benefits of a Microlon Engine Treatment.

NOTE: Microlon is compatible with all oils & fuels including synthetics.

Microlon, Inc 217 Trademark Dr. Buda, Texas 78610 USA
Order Desk: (512) 295-9895 Toll Free Order Desk: (800) 962-4152
Tech Support: (512) 247-8172 FAX: (512) 295-9896